## Ultra Pro™ Ultrasound Table - Comfort Focused Design for Quality Imaging

## 058-720 058-725

## BIODEX ULTRA PRO ULTRASOUND TABLE, 115 VAC BIODEX ULTRA PRO ULTRASOUND TABLE, 230 VAC

- · Dimensions:
  - Overall: 70" I x 30" w (177.8 x 76.2 cm); 35" w (88.9 cm) with optional side rails
  - Drop-Down Leg Section: 12.6" I (32 cm)
- Motions:
  - Height Adjustable: 23" to 39" (58.4 to 99 cm)
  - Trendelenburg: 0° to ±15°
  - Fowler Back: 0° to 80° infinitely adjustable
- Controls:
  - Hand Control: Activates height, Trendelenburg motions Fowler positioning and auto level motions
  - Foot Control (optional): Activates height, Trendelenburg motions, and Fowler positioning
- Wheels: 5" (12.7 cm) Individual locking swivel casters; central floor-locking system
- Tabletop: Three primary sections: torso section with Fowler positioning, center section remains fixed and leg section drops down to 40° and 80° for stirrup access
- Mattress: Torso section 2" (5 cm) thick, center and leg sections 3" (8 cm) thick; Naugahyde®, antimicrobial mattress cover with Advanced BeautyGard® provides protection against bacteria
- · Upholstery Color: Graphite
- Patient Restraints: Two body straps
- · Finish: Powder coat
- Patient Capacity: 500 lb (227 kg); weight tested to four times the patient load rating.
- Weight: 335 lb (152 kg)
- Power: 115 VAC or 230 VAC
- Certifications: ETL and cETL Listed to UL60601-1 and CAN/CSA C22.2
  No. 601.1-M90 and EN 60601-1 standards.
- Warranty: Two years parts and labor





